



SPECIFICATIONS FOR ADDITIONS ,ALTERATIONS AND GARAGES
(To Be Completed and Returned with Building Permit Application)

FOUNDATION SIZE: _____ DEEP _____ WIDE _____

EXTERIOR WALL CONSTRUCTION:

STUD SIZE: _____ SPACING: _____ O.C. (CIRCLE ONE)

PLATES: _____ HEADERS: _____

2-2X12'S REQUIRED OVER 16' GARAGE DOOR

SHEATHING: _____ THICKNESS: _____ CORNER BRACING 1"X4"

Only omit if wood sheathing is used

SIDING: _____

CEILING CONSTRUCTION:

WOOD JOISTS _____ O.C. _____ SPAM _____

BRIDGING: _____

FINISH CEILING MATERIAL: _____

ROOF CONSTRUCTION:

ROOF PTICH: _____

RAFTERS: SIZE: _____ SPACING _____ O.C. _____

ROOF SHEATHING: _____ SHINGLES: _____

15 LB. SATURATED FELT REQUIRED UNDER SHINGLES ON ALL ROOFS

INTERIOR WALL CONSTRUCTION:

DRYWALL: (MATERIAL) _____ THICKNESS _____

OTHER: (DESCRIBE) _____ THICKNESS _____

WOOD FLOOR CONSTRUCTION:

FLOOR JOISTS _____ O.C. _____ SPAM _____

SUB FLOOR _____ FINISH FLOOR _____

BRIDGING _____

EXTERIOR DOOR: SIZE: _____ X _____ THICK

SIZE: _____ X _____ THICK

GARAGE OVERHEAD DOOR: SIZE: _____ X _____ THICK